





Pavimentos Laminados y SPC































Rocko SPC 1210x192x5+1IXPE















AC6





ROCKO









HS R073 Scandipure

HS R077 Barista

HS R078 Airflow



SO R082 Humidor



Organic Long 2003x195x8































RO K284 Summer Breeze Oak



HO K451 Silverdale Oak



VH 8156 Red River Hickory



RO K327 Hillside Oak



HO K287 Steelworks Oak



HO K450 Firebrand Oak









Binyl Pro 1285x192x8























EN 13329





PO 1517 Fairland Oak



RF 1530 Dartagnan Oak



NL 1531 Aramis Oak

LP1514 Svalbard Oak



TO 1533 Hamilton Oak



NL 1536 Stockholm Oak



HC 1539 Clayborne Oak



LP 1579 Havana Oak





Altitude More 2000x242x12























EN 13329



HO 5954 Hardy Oak



RO K326 Sundance Oak



VH 8155 Appalachian Hickory



Krono5 V4 1285x192x8













EN 13330



NL K057 Clearwater Oak



NL 5946 Rockford Oak



UW 8575 Blonde Oak



NL K338 Credenza Oak



UW 8714 Nevada Oak



Super Natural 1285x192x8















GT 5985 Sherwood Oak



NL 5946 Rockford Oak



NL 5966 Khaki Oak



LP 8575 Blonde Oak



LP 8573 Harlech Oak

SUPER NATURAL

















Aqualine Master Floor 8.0 8x1383x193mm


















AV K4420 Evoke Classic



EG K2241 Cordoba Crema



AV K5573 Evoke Coast



AV K4442 Historic Arctic





Logística

Logistica						
COLECCIÓN	MEDIDAS	ESPESOR	LAMAS CAJA	M2 CAJA	CAJAS x PALLET	M2 PALLET
Rocko Classic	1210 x 192 mm	5+1 mm	7	1,63	72	117,09
Organic Long	2003 x 195 mm	8 mm	7	2,73	40	109,36
Bionyl Pro	1285 x 192 mm	8 mm	9	2,22	52	115,46
Altitude More	2000 x 242 mm	12 mm	4	1,94	36	69,7
Krono5 V4	1285 x 192 mm	8 mm	9	2,22	52	115,46
Super Natural	1285 x 192 mm	8 mm	9	2,22	52	115,46
Masterfloor	1383 x 193 mm	8 mm	9	2,40	52	124,92

Accesorios **MODELO** Rodapié Junta Dilatación Junta Desnivel





All floors are put through a series of rigorous tests in order to comply with international quality standards, which is why we grant an extensive residential warranty with every product.



This flooring is amazingly robust due to its super durable surface. Moving furniture or falling objects are not a problem because of its high pressure and impact resistance.



Bevelled edges on all four sides of the plank ensure an authentic floorboard appearance.



Due to its flexible design layer, the flooring has comfortable haptics and is warm underfoot.



Inspired by traditional craftsmanship, the elegant design of the rounded joints provides a timeless



Safety is something we put great emphasis on. Classification in anti-slip classes has been achieved through specially developed surface structures, which address the requirements for floor coverings in the workplace and commercial areas



A.B.C. Anti Bacterial Comfort inhibits the growth

of bacteria on your flooring and provides you with

the peace of mind that comes from a healthy home

environment. (Tested germs: Staphylococcus aureus).



where a high risk of slipping is present. Classification: R9 and R10 according to DIN 51330,





A: according to DIN 51097



The synchronous pores follow the grain of the decor. meaning they flawlessly mimic the character of natural wood.



Up to 60 different panels on digitally printed design





are possible. This lends your flooring an authentic appearance that is virtually free of repetition.



The robust surface protects your flooring against microscratches that can be caused by strong mechanical stresses or the claws of house pets.



The flooring has a soft surface and feels very com-



Thanks to the robust surface, which is also undaunted by small mishaps, the flooring is exceptionally well-suited for life with house-pets.



This floor is made from real wood. The high-quality





brushed oak surface gives every room natural elegance.



The flooring is light-resistant (rated at 6, the top of the blue wool scale).



The flooring provides complete protection against unpleasant shocks. The Anti-Static is built-in and guaranteed for the life of the floor.



Due to an integrated pad, the flooring reduces impact sound, echoes and vibrations. An additional underlay is not required, which saves time and money.





